

GAS AND VACUUM SEALERS



STANDARD WITH GAS FLUSH FOR NITROGEN, ARGON AND CO2

WWW.HIGHNITRO.COM
info@highnitro.com +1 252 206 7901

BOXER

Fully equipped, complete series of table-tops to vacuum seal and store your produce in bags or jars. Standard with sensor and gas.

BOXER 42XL

889 cf/h (25 m³/h)

MACHINE DIMENSIONS

24.2" x 19.4" x 17.3"



CART

Full stainless steel model with castors and shelf
23.8" x 18.9" x 26.5"



BOXER 52

889 cf/h (25 m³/h)

MACHINE DIMENSIONS

20.8" x 27.5" x 17.3"



POLAR

Single and double chamber vacuum and gas sealers with a flat work plate and an extensive range of options. Standard with sensor and gas.


POLAR 80

MACHINE DIMENSIONS

31.1" x 35.4" x 43.3"

PUMP CAPACITY

4,237 cf/h (120 m³/h)




POLAR 2-50

MACHINE DIMENSIONS

36.2" x 58.7" x 43"

PUMP CAPACITY

4,237 cf/h (120 m³/h)



OPTIONS

Liquid control

Automatic lid (P2-85/P2-95)

Extra high lid (P2-85)

POLAR 2-75

MACHINE DIMENSIONS

47.4" x 58.4" x 52.8"

PUMP CAPACITY

6,709 cf/h (190 m³/h)





POLAR 2-85/2-95

MACHINE DIMENSIONS

51" x 74.8" x 57" (P2-85)
47.7" x 95.3" x 62.8" (P2-95)

PUMP CAPACITY

12,713 cf/h (360 m³/h)



MARLIN


Perfect for sealing and storing high volumes of produce. Standard with sensor and gas.

MARLIN 52II

2,780 cf/h (75 m³/h)

MACHINE DIMENSIONS


28" x 27.4" x 40.4"





GAS FLUSH

For nitrogen, argon and CO2.
Standard on all Storabis sealers



Adding a gas, whether it's nitrogen argon or a mix, precisely extends the shelf life of the flower.

Furthermore, it preserves the quality and even cures the produce when packed.

In case of adding a gas, the use of vacuum bags is recommended.

WWW.HIGHNITRO.ORG
info@highnitro.com
+1 252 206 7901

COMBIVAC CONTROL

Including Jars function.
Standard on all Storabis sealers

The CombiVac control system is the future of control. It includes the new Jars function and offers several options to upgrade and optimize sealing and storage.

SECURE OPERATION

- 20 program memory
- Standard Sensor control
- Full color 4.7" LCD screen
- Data storage
- Compatible with label printer
- USB connection
- Export usage log
- Multilevel access (operator, owner, dealer or service agent, factory)

OPTIONS & FUNCTIONS

- Liquid control for vacuum sealing liquids (optional)
- External vacuum
- Different seal systems and seal bar configurations
- Gas flush for N2, CO2 or Argon packaging

SERVICE

- Oil warning indicator
- Easy Service tool
- Pump maintenance program

COMBIVAC CONTROL

Standard with Sensor control, Jars function and 20 program memory



SUITABLE FOR ALL GASES EXCEPT OXYGEN

IN CONTROL

In control of the vacuum packaging cycle. Anytime.
For a guaranteed and maximum end vacuum of 99.8%.



SENSOR CONTROL

The extraction of air stops as soon as the preset vacuum percentage in the chamber has been reached. For secure, fast and optimal packaging. Sensor control is standard on all models.



GAS FLUSH

Prior to the sealing of the bag, a gas can be injected. Adding CO2, nitrogen, argon or a mix of both gases, increases the product's shelf life, offers extra protection and prevents the product from coloring.

ACCESSORIES



LABEL PRINTER

Including label dispenser, 1 roll of labels, cables and configuration (only in combination with ACS)



SERVICE KIT

For primary maintenance, including seal wires, teflon tape and teflon band, lid gasket, oil for the pump and a silicone profile for the contra bar. Available as an after-sales part or in combination with machines.